

Motorne zaštitne sklopke GV serije



G3GE3



G3GE3

Prednosti:


- jednostavna i brza montaža na DIN letvu
- nadstrujno termički i magnetsko kratkospojni okidač
- kratkospojni okidač $12 \times I_n$
- osetljivost na ispad faze u skladu sa IEC/EN 60947-4-1
- temperaturna kompenzacija

Tehnički podaci

Izvedba	IEC60947-2, IEC60947-4-1
Nominalni napon	660V 50/60Hz
Nominalna struja	80A
Temperaturno područje	-25 °C do 40 °C
Zaštita od ispada faza	po IEC60947-4-1
Pribor	pomoćni kontakti
Kućišta	IP 55

Područje primene

Za osiguranje motornih pogona



Motorne zaštitne sklopke GV serije

Type	Standard power ratings of 3-phase motors 50 / 60Hz in category AC-3						Setting range
	220V	380V	415V	440V	500V	660V	
	KW	KW	KW	KW	KW	KW	
GV1-M01	--	--	--	--	--	--	0.1-0.16
GV1-M02	--	--	--	--	--	--	0.16-0.25
GV1-M03	--	--	--	--	--	--	0.25-0.4
GV1-M04	--	--	--	--	--	0.37	0.4-0.63
GV1-M05	--	--	--	0.37	0.37	0.55	0.63-1
GV1-M06	--	0.37	--	0.55	0.75	1.1	1-1.6
GV1-M07	0.37	0.75	1.1	1.1	1.1	1.5	1.6-2.5
GV1-M08	0.75	1.5	1.5	1.5	2.2	3	2.5-4
GV1-M10	1.1	2.2	2.2	3	3.7	4	4-6
GV1-M14	2.2	4	4	4	5.5	7.5	6-10
GV1-M20	4	7.5	7.5	7.5	10	11	10-16
GV1-M21	5.5	10	9	9	11	15	16-20
GV1-M22	5.5	11	11	11	15	18.5	20-25
GV2-M01 / RS01	--	--	--	--	--	--	0.1-0.16
GV2-M02 / RS02	--	--	--	--	--	--	0.16-0.25
GV2-M03 / RS03	--	--	--	--	--	--	0.25-0.4
GV2-M04 / RS04	--	--	--	--	--	0.37	0.4-0.63
GV2-M05 / RS05	--	--	--	0.37	0.37	0.55	0.63-1
GV2-M06 / RS06	--	0.37	--	0.55	0.75	1.1	1-1.6
GV2-M07 / RS07	0.37	0.75	0.75	1.1	1.1	1.5	1.6-2.5
GV2-M08 / RS08	0.75	1.5	1.5	1.5	2.2	3	2.5-4
GV2-M09 / RS09	1.1	2.2	2.2	3	3.7	4	4-6
GV2-M10 / RS10	2.2	4	4	4	5.5	7.5	6-10
GV2-M14 / RS14	4	7.5	7.5	7.5	10	11	10-16
GV2-M16 / RS16	3	5.5	5.5	7.5	7.5	9	9-14
GV2-M20 / RS20	4	7.5	9	9	9	11	13-18
GV2-M21 / RS21	5.5	11	11	11	11	15	17-23
GV2-M22 / RS22	5.5	11	11	11	15	18.5	20-25
GV2-M32 / RS32	7.5	15	15	15	18.5	26	24-32
GV3-M06	--	0.37	--	0.55	0.75	1.1	1-1.6
GV3-M07	0.37	0.75	1.1	1.1	1.1	1.5	1.6-2.5
GV3-M08	0.75	1.5	1.5	1.5	2.2	3	2.5-4
GV3-M10	1.1	2.2	2.2	3	3.7	4	4-6
GV3-M14	2.2	4	4	4	5.5	7.5	6-10
GV3-M20	4	7.5	7.5	7.5	10	11	10-16
GV3-M25	5.5	11	11	11	15	18.5	16-25
GV3-M40	11	18.5	18.5	22	25	33	25-40
GV3-M63	15	30	33	33	40	55	40-63
GV3-M80	22	40	45	45	55	63	56-80